

United States
Department of
Agriculture

Forest Service




Southern
Research Station

General Technical
Report SRS-122

Numerical Details and SAS Programs for Parameter Recovery of the S_B Distribution

Bernard R. Parresol, Teresa Fidalgo Fonseca,
and Carlos Pacheco Marques



The Authors:

Bernard R. Parresol, Mathematical Statistician, U.S. Department of Agriculture, Forest Service, Southern Research Station, Biometrics Unit, Asheville, NC 28804; **Teresa Fidalgo Fonseca** and **Carlos Pacheco Marques**, Faculty, Universidade de Trás-os-Montes e Alto Douro, Departamento de Ciências Florestais e Arquitectura Paisagista, Apartado 1013, 5001-801 Vila Real, Portugal.

Cover: Pine stand profile and graphical display of the observed d.b.h. distribution (histogram) and the S_B fitted distribution function (solid line).

June 2010

Southern Research Station
200 W.T. Weaver Blvd.
Asheville, NC 28804

Numerical Details and SAS Programs for Parameter Recovery of the S_B Distribution

**Bernard R. Parresol, Teresa Fidalgo Fonseca,
and Carlos Pacheco Marques**

Contents

	<i>Page</i>
List of Figures	iv
Introduction	1
The S_B Distribution	1
Parameter Recovery	2
Three-Parameter Recovery System	2
All-Parameter Recovery System	3
Procedures for Solving the Parameter Recovery Systems	3
Levenberg-Marquardt Algorithm	4
Global Minimum, Convergence, and Initial Values	4
Parameter Restrictions	5
Restricted Estimation	5
Statistical Analysis System Programs	6
S_B Recovery 3parm	6
S_B Recovery 4parm	6
Examples and Discussion	7
S_B Recovery 3parm	7
S_B Recovery 4parm	8
Concluding Remarks	12
Acknowledgments	12
Literature Cited	12
Appendix A —SAS Source Code for S_B Recovery 3parm	15
Appendix B —SAS Source Code for S_B Recovery 4parm	21

List of Figures

	<i>Page</i>
Figure 1 —Johnson S_B distributions with various values of the γ and δ shape parameters. (A) displays unimodal shapes (right-skewed for $\gamma = 1$, symmetric for $\gamma = 0$, left-skewed for $\gamma = -1$). (B) displays a reverse-J shaped distribution and a bimodal distribution	2
Figure 2 —Input file used on S_B Recovery 3parm program	7
Figure 3 —Output file created by S_B Recovery 3parm program	7
Figure 4 —Observed frequencies and S_B simulated distributions using the three-parameter recovery program. (A) Observation “S0204” is a classic right-skewed unimodal fit. In (B) observation “S1104” and (C) observation “S1606” we see reasonable bimodal fits to the observed frequencies. (D) observation “S1906” shows an excellent fit to the reverse-J shaped distribution	8
Figure 5 —Input file used on S_B Recovery 4parm program	9
Figure 6 —Output file created by S_B Recovery 4parm program	9
Figure 7 —Observed frequencies and S_B simulated distribution for observation “S2504” using the initial solution of the all-parameter recovery program	9
Figure 8 —Updated initial values used on S_B Recovery 4parm program	10
Figure 9 —Output file created by S_B Recovery 4parm program for the new run with updated initial values	10
Figure 10 —Observed frequencies and S_B simulated distributions using the updated output values of the all-parameter recovery program. All four graphs (A-D) display good fits to the observed frequencies	11
Figure 11 —Observed frequencies and S_B simulated distribution for observation “S1104” using the all-parameter recovery program	11

Numerical Details and SAS Programs for Parameter Recovery of the S_B Distribution

Bernard R. Parresol, Teresa Fidalgo Fonseca, and Carlos Pacheco Marques

Abstract

The four-parameter S_B distribution has seen widespread use in growth-and-yield modeling because it covers a broad spectrum of shapes, fitting both positively and negatively skewed data and bimodal configurations. Two recent parameter recovery schemes, an approach whereby characteristics of a statistical distribution are equated with attributes of a stand in order to solve for the parameters of the distribution, are described for the S_B . The first scheme permits recovery of the range and both shape parameters, but the location parameter must be *a priori* specified. The second scheme is an all-parameter recovery model. The details of the parameter recovery models, that is the system of equations with their concomitant constraints, are laid out. A solution technique for the constrained parameter recovery models that uses the Kuhn-Tucker conditions, the Lagrange function, and the Levenberg-Marquardt algorithm is briefly reviewed. Two Statistical Analysis System programs that implement the parameter recovery models, S_B Recovery 3parm and S_B Recovery 4parm, are listed and demonstrated with instructive examples.

Keywords: Basal area-size distribution, constraint functions, diameter distributions, moments, nonlinear programming problem, restricted estimation.

Introduction

Forecasting number of trees in a stand over diameter classes is customarily done through the use of probability density functions (PDF). Many distributions have been utilized such as the beta, Weibull, gamma, and lognormal. Hafley and Schreuder (1977) examined the skewness and kurtosis of various statistical distributions as a measure of the flexibility of the distributions in regard to their changes in shape. They showed that the four-parameter S_B PDF (Johnson 1949, S_B means system bounded) provides greater generality in terms of skewness and kurtosis than many of the usually applied distributions in forestry. Based on Hafley and Schreuder's findings, many growth-and-yield models that used the S_B distribution ensued (e.g., Fonseca 2004, Hafley and Buford 1985, Kamziah and others 1999, Kiviste and others 2003, Lopes 2001, Parresol 2003, Tham 1988, Von Gadow 1983).

A variety of parameter estimation methods are available for the S_B distribution, such as the percentile method, linear and nonlinear regression methods, moments, and maximum likelihood. These have been reviewed and compared by Zhou and McTague (1996) and Kamziah and others (1999). The state-of-the-art approach for parameter estimation in growth-and-yield-modeling is called parameter recovery (Hyink and Moser 1983). Parresol (2003) presented a loblolly pine (*Pinus taeda* L.) growth-and-yield model using the S_B distribution where one parameter of the distribution was fixed and the remaining three parameters were estimated in a parameter-recovery context. Parresol's new methodology was more general than previous S_B -based growth-and-yield-models which recovered only one or two parameters (e.g., Newberry and Burk 1985, Parresol 1983, Scolforo and Thierschi 1998). Fonseca (2004) and Fonseca and others (2009) extended Parresol's scheme to create a methodology that completely recovers Johnson's S_B diameter distribution from stand variables. The objectives of this article are (1) to present the details necessary to implement the three-parameter recovery scheme of Parresol (2003) and the all-parameter recovery scheme of Fonseca (2004) and Fonseca and others (2009) and (2) to present and demonstrate the Statistical Analysis System (SAS) programs that employ these schemes.

The S_B Distribution

Let the random variable D represent tree diameter, and let d stand for particular values from the range of D . The equation for Johnson's S_B distribution for tree diameter is

$$f(d) = \begin{cases} \frac{\delta\lambda}{\sqrt{2\pi}(d-\xi)(\xi+\lambda-d)} \exp\left\{-\frac{1}{2}\left[\gamma + \delta \ln\left(\frac{d-\xi}{\xi+\lambda-d}\right)\right]^2\right\}, & \xi < d < \xi + \lambda, \delta > 0, -\infty < \gamma < \infty, \lambda > 0, \xi \geq 0 \\ 0 & \text{otherwise} \end{cases} \quad (1)$$

It is characterized by the location parameter ξ , the range parameter λ , and shape parameters γ and δ . Although there is no closed form expression for its cumulative distribution function, if $D \sim S_B(\xi, \lambda, \gamma, \delta)$ then

$$z = \gamma + \delta \ln\left[\frac{(d - \xi)}{(\xi + \lambda - d)}\right] \sim \mathcal{N}(0,1) \quad (2)$$

z being a standard normal deviate. This property means integration of equation (1), i.e., the S_B PDF, over specific classes can be accomplished by application of the well-tabulated standard normal distribution. It is easy to show that the shape of the distribution of D depends only on the parameters γ and δ . For, defining a new variable

$$y = f(d) = (d - \xi) / \lambda \quad (3)$$

it follows from equation (2) that

$$z_y = \gamma + \delta \ln\left[\frac{y}{1-y}\right] \sim \mathcal{N}(0,1) \quad (4)$$

and Y must have a distribution of the same shape as D (Johnson and Kotz 1970).

Figure 1 shows a number of the possible shapes that the S_B distribution can assume. Often stands display a unimodal shape in the range of tree diameters, as displayed in figure 1A. The first line is a right or positively skewed shape, which occurs when γ has a positive value. The middle line is a symmetric shape, like a normal curve, which occurs when γ is zero. The third line is a left or negatively skewed shape, which occurs when γ takes on a negative value. Figure 1B shows other shapes that the S_B distribution can assume. Uneven-aged stands typically have a reverse-J shape to the distribution of tree diameters. As seen in the graph, bimodal shapes are possible with the S_B distribution, as might occur with a storm-damaged stand where most of the overstory is taken out but some large trees survive.

Parameter Recovery

The parameter recovery approach uses stand-average attributes such as the mean diameter and basal area per unit area to obtain estimates of the underlying diameter distribution (Hyink and Moser 1983). The fundamental idea is to relate characteristics of an assumed distribution (in our case the S_B), such as percentile points or moments, with attributes of the stand and, thereby, recover the parameters of the distribution that would yield those exact values.

Put another way, in the parameter recovery method, the parameters of the distribution function are solved from a system of equations, equating (measured or predicted) stand attributes to their analytical counterparts (Kangas and Maltamos 2000).

Three-Parameter Recovery System

In Parresol (2003) a parameter recovery model for the range and shape parameters was developed that uses the median and the first and second noncentral moments of




Figure 1—Johnson S_B distributions with various values of the γ and δ shape parameters. (A) displays unimodal shapes (right-skewed for $\gamma = 1$, symmetric for $\gamma = 0$, left-skewed for $\gamma = -1$). (B) displays a reverse-J shaped distribution and a bimodal distribution.

the diameter distribution (average diameter and quadratic mean diameter). The ξ parameter is *a priori* specified. Parresol showed that the γ parameter could be expressed as a function of the other three parameters

$$\gamma = \delta \ln \left[\frac{\lambda}{(d_{\text{median}} - \xi)} - 1 \right] \quad (5)$$

where

d_{median} is the median tree diameter or 50th percentile of the diameter distribution. This allowed for a system of two equations in two unknowns to recover the range and both shape parameters.

$$\bar{d} = \xi + \lambda \mu'_1(y) \quad (6)$$

$$B = \mathcal{K} N \left[\xi^2 + 2\xi \lambda \mu'_1(y) + \lambda^2 \mu'_2(y) \right] \quad (7)$$

where

\bar{d} = average stand diameter

B = basal area per unit area

N = trees per unit area

\mathcal{K} = units conversion ($\pi/40\,000$ for metric units and $\pi/576$ for English units)

$\mu'_1(y)$ = first noncentral moment of the distribution of Y , and

$\mu'_2(y)$ = second noncentral moment of the distribution of Y

As mentioned, ξ is prespecified, λ and δ are iteratively solved for using equations (6) and (7), and then γ is solved for using equation (5). For details of the derivation of the three-parameter recovery model see Parresol (2003).

All-Parameter Recovery System

Fonseca (2004), working with maritime pine (*P. pinaster* Aiton) diameter distributions, extended the three-parameter recovery scheme to create a methodology that recovers all four parameters of Johnson's S_B distribution from stand variables. In order to recover all the parameters it is necessary to supplement equations (5), (6), and (7) with an additional function. The idea behind parameter recovery is to use values from the statistical distribution that (a) directly relate to stand characteristics, (b) are quantities that foresters can understand, and (c) have a meaningful interpretation. As already stated, the first noncentral moment of statistical distributions is directly related to average stand diameter, and the second noncentral moment is readily understood

as quadratic mean diameter, i.e., the tree of average basal area that we will designate as d_q . A paper by Gove and Patil (1998) gives a meaningful interpretation of the third noncentral moment of statistical distributions as it relates to stand diameter. Specifically, understanding arises when diameter distributions are viewed with respect to tree basal area (basal area-size distribution or BASD) rather than to tree frequency. Designating the BASD mean as \bar{d}_B , the third noncentral moment of the diameter distribution is the product of the mean BASD and the square of the quadratic mean diameter, that is, $\mu'_3(d) = \bar{d}_B d_q^2$. Using this property, Fonseca derived the following formula for the S_B distribution:

$$\bar{d}_B d_q^2 = \xi^3 + 3\xi^2 \lambda \mu'_1(y) + 3\xi \lambda^2 \mu'_2(y) + \lambda^3 \mu'_3(y) \quad (8)$$

Inclusion of equation (8) in Parresol's (2003) earlier system allows for the ξ parameter also to be recovered. An estimate of the third noncentral moment of diameter distribution can be calculated from plot diameters as follows:

$$\hat{\mu}'_3(d) = \frac{\sum_{i=1}^n d_i^3}{n} \quad (9)$$

where

n = number of trees on the plot

For details on the development of the all-parameter recovery model please refer to Fonseca (2004) and Fonseca and others (2009).

Procedures for Solving the Parameter Recovery Systems

The S_B parameter recovery strategies involve solving complex systems of nonlinear equations. Parresol's scheme uses two nonlinear equations in two unknowns and Fonseca's scheme is based on three nonlinear equations in three unknowns. By subtracting the left-hand sides of equations (6), (7), and (8) we equate the functions to zero. By squaring the functions we create a system whereby we can use a nonlinear least-squares minimization routine. A least-squares problem is a special form of minimization problem where the objective function (the function to be minimized) is defined as a sum of squares of other functions (in our case nonlinear functions).

$$F(\mathbf{x}) = \frac{1}{2} [f_1^2(\mathbf{x}) + \dots + f_m^2(\mathbf{x})] \quad (10)$$

where

$\mathbf{x} = (x_1, x_2, \dots, x_p)$ is a vector of p unknown parameters and $m \geq p$

There are several minimization techniques available to solve for nonlinear systems. The Levenberg-Marquardt (LM) algorithm is one that works well on many practical problems and, thus, is a sensible choice.

Levenberg-Marquardt Algorithm

Starting with an initial value vector \mathbf{x} (a guess) to the solution, the LM iterative update formula is (Ralston and Rabinowitz 1978, page 363)

$$\mathbf{x}_{i+1} = \mathbf{x}_i - (\mathbf{J}'_i \mathbf{J}_i + \theta_i \mathbf{I})^{-1} \mathbf{J}'_i \mathbf{f}_i \quad (11)$$

where

$\theta_i \geq 0$ = a scaling factor
 \mathbf{I} = an identity matrix, and
the Jacobian at each iteration point \mathbf{x}_i is

$$\mathbf{J}_i = \left(\frac{\partial f_j}{\partial x^{(k)}} \right)_{\mathbf{x}=\mathbf{x}_i} \quad (12)$$

The Jacobian is a matrix of partial derivatives. For the three-parameter recovery system the partial derivatives are given in Parresol (2003). For the all-parameter recovery system the partial derivatives are given in Fonseca and others (2009). The LM algorithm is a blend of gradient descent (also called steepest descent) and Gauss-Newton iteration. For a detailed explanation of the LM algorithm and its advantages see Ralston and Rabinowitz (1978) and Ranganathan (2004).

Global Minimum, Convergence, and Initial Values

All optimization algorithms converge towards local rather than global optima. The smallest local minimum of an objective function is called the global minimum, and the goal is to find the solution vector that returns the global minimum of the objective function. For the S_B parameter recovery models the absolute minimum of the objective

equation (10) is zero, but the global minimum may be greater than zero due to constraints imposed on the solution. From optimization theory (see Avriel 2003), a local minimizer $\tilde{\mathbf{x}}$ satisfies the following three conditions:

1. There exists a small, feasible neighborhood of $\tilde{\mathbf{x}}$ that does not contain any point \mathbf{x} with a smaller function value $F(\mathbf{x}) < F(\tilde{\mathbf{x}})$.
2. The vector of first derivatives (gradient) $\mathbf{g}(\tilde{\mathbf{x}}) = \nabla F(\tilde{\mathbf{x}})$ of the objective function F (projected toward the feasible region) at the point $\tilde{\mathbf{x}}$ is zero.
3. The matrix of second derivatives $\mathbf{G}(\tilde{\mathbf{x}}) = \nabla^2 F(\tilde{\mathbf{x}})$ (Hessian matrix) of the objective function F (projected toward the feasible region) at the point $\tilde{\mathbf{x}}$ is positive definite.

One reason for choosing the LM algorithm is that for $\theta_i > 0$ the inverse matrix in equation (11) always exists and condition 3 is always met. Condition 2 gives us a convenient convergence criterion to stop the iteration of equation (11) and declare that a local minimizer $\tilde{\mathbf{x}}$ has been found. Termination requires the gradient to vanish, or in mathematical terms, that the maximum absolute gradient element be very small, such as

$$\max_j |g_j(x^{(k)})| \leq 10^{-5} \quad (13)$$

Other definitions of convergence can be used. For example, terminate when the Euclidean distance between parameter vectors in consecutive iterations is smaller than a critical value such as 10^{-8} . Multiple tests for convergence are typically used with optimization routines. To check that we are at the global minimum we need to compute the L_1 norm

$$\|\mathbf{f}(\tilde{\mathbf{x}})\|_1 = \sum_{i=1}^m |f_i(\tilde{\mathbf{x}})| \quad (14)$$

and verify that it is close to zero. It is a good idea to run various optimizations with a pattern of different starting values to check that the global minimum is obtained. If the optimization routine fails, i.e., condition 1 is not met or the maximum number of iterations is exceeded, simply use different starting values.

Initial values are required to start the iteration of equation (11). Normally information from inventory data is available

to help guide us in choosing good starting values. We can take the observed minimum and maximum diameters and use their difference as an initial guess for the range parameter λ . For the location parameter ξ , a scalar multiple such as 0.5 to 0.8 of the observed minimum diameter gives a reasonable initial value. Concerning the shape parameter δ , for bimodal shapes use a starting value ≤ 0.7 and for unimodal shapes use an initial value ≥ 1 .

Parameter Restrictions

To prevent the LM algorithm [equation (11)] from projecting the parameter vector \mathbf{x} into an unfeasible parameter space, it is necessary to impose restrictions on the parameters. Constraints on the parameter space can also prevent unreasonable solutions from occurring. It is important to note that constraints can be equality restrictions or inequality restrictions of the form \leq or \geq , but not $<$ or $>$.

Three-parameter recovery system—The constraints are constructed as follows. From equation (5) we know that $\gamma = \delta \ln [\lambda / (d_{\text{median}} - \xi) - 1]$, and this equation reveals that $\lambda / (d_{\text{median}} - \xi) > 1$ to avoid an illegal log argument, thus $d_{\text{median}} - \xi < \lambda$. As a practical matter the range should be restricted. A reasonable upper bound is $2 \times$ initial guess for λ . By definition of the S_B distribution, $\delta > 0$. From all this we have

$$\begin{aligned} d_{\text{median}} - \xi < \lambda \leq 2 \times \text{initial } \lambda \text{ value} \\ 0 < \delta \end{aligned} \quad (15)$$

Because constraints must be expressed as \leq or \geq , we need to make small adjustments in equation (15). Our final constraints are

$$\begin{aligned} d_{\text{median}} - \xi + 0.01 \leq \lambda \leq 2 \times \text{initial } \lambda \text{ value} \\ 0.01 \leq \delta \end{aligned} \quad (16)$$

All-parameter recovery system—For this system we need both boundary conditions and a linear constraint. In this system ξ is a random parameter. Again, consider the equation $\gamma = \delta \ln [\lambda / (d_{\text{median}} - \xi) - 1]$. It is obvious that ξ must be less than d_{median} to avoid an illegal log argument. We know that ξ cannot be less than zero, hence $0 \leq \xi < d_{\text{median}}$. Alternatively, one can use observed minimum diameter as an upper bound constraint for ξ . The

equation also reveals that $\lambda / (d_{\text{median}} - \xi) > 1$ to avoid an illegal log argument, thus $d_{\text{median}} - \xi < \lambda$. Because ξ and λ are random parameters, this gives the linear restriction $\xi + \lambda > d_{\text{median}}$. As before we want to restrict the range and we know that $\delta > 0$. Gathering all this information gives

$$\begin{aligned} 0 \leq \xi < d_{\text{median}} \\ \lambda \leq 2 \times \text{initial } \lambda \text{ value} \\ 0 < \delta \\ \xi + \lambda > d_{\text{median}} \end{aligned} \quad (17)$$

We need to make small adjustments in equation (17) to create the necessary \leq and \geq inequalities. Our final constraints are

$$\begin{aligned} 0 \leq \xi \leq d_{\text{median}} - 0.01 \\ \lambda \leq 2 \times \text{initial } \lambda \text{ value} \\ 0.01 \leq \delta \\ \xi + \lambda \geq d_{\text{median}} + 0.01 \end{aligned} \quad (18)$$

Restricted Estimation

From the previous section we showed that some of the S_B parameters are subject to boundary constraints and that ξ and λ are subject to a linear restriction when recovering all parameters. The Kuhn-Tucker theorem (Avriel 2003, Kuhn and Tucker 1951) is a theorem in nonlinear programming which states that if a regularity condition holds and the objective function F and constraint functions c_i are convex, then a solution $\tilde{\mathbf{x}}$ which satisfies the conditions c_i for a vector of multipliers α is a local optimum (a minimum or maximum depending on the problem). The Kuhn-Tucker theorem is a generalization of Lagrange multipliers. The linear combination of objective and constraint functions

$$L(\mathbf{x}, \alpha) = F(\mathbf{x}) - \sum \alpha_i c_i(\mathbf{x}) \quad (19)$$

is the Lagrange function and the coefficients α_i are the Lagrange multipliers. Because of constraints on the parameters in both recovery systems, we will actually minimize the Lagrange function [equation (19)], and the three conditions for a local minimizer $\tilde{\mathbf{x}}$ still apply.

Statistical Analysis System Programs

We developed two SAS, version 9.1, programs that utilize the nonlinear programming Levenberg-Marquardt (NLPLM) procedure, part of the interactive matrix language (IML) capabilities of SAS software (SAS Institute Inc. 2004, pages 795–798). The first program, S_B Recovery 3parm, is listed in appendix A. The second program, S_B Recovery 4parm, is given in appendix B. While the two programs share the same structure, there are differences in the input needed, in the makeup of the constraint matrix, and in the system of equations to be solved. Hence, we felt it would be better to create two separate programs rather than one program with dichotomies. It is important to note that the programs can use either the international system of units (the metric system) or the English system of units. For input and output values in the metric system, use the \mathcal{K} -value on line 207 of S_B Recovery 3parm (line 206 should start with an * to make it a comment line) and on line 246 of S_B Recovery 4parm (line 245 should start with an * to make it a comment line). Likewise, for input and output values in the English system, use the \mathcal{K} -value on line 206 of S_B Recovery 3parm (line 207 should start with an * to make it a comment line) and on line 245 of S_B Recovery 4parm (line 246 should start with an * to make it a comment line).

S_B Recovery 3parm

This program is designed to input required data through an Excel[®] (Microsoft Corporation) file. The file location and name are specified by the user on line 53 of the program (see appendix A). The program checks the validity of the initial values in a “do loop” on lines 254–259. On line 59 the user can supply a descriptive project title that will print on the top of all printed output from the program. The amount of printed output is controlled by the options vector on line 210. The value of the second element of the vector controls the output from the NLPLM procedure. A value of zero turns off output. A value of 1 turns on summaries and iteration history. More output can be generated using values 2–5, but generally the summary and iteration history are more than sufficient. See the SAS/IML[®] 9.1 “User’s Guide” for more information on the options vector (SAS Institute Inc. 2004, pages 343–349). The constraint matrix is initialized on line 238. Lines 261–268 actually set the bounds for λ in the matrix. At the user’s discretion, on line 263 a smaller or larger upper bound can be specified for λ , but generally $2 \times$ initial value works well. The

NLPLM procedure gives a return code (RC) that indicates the termination criterion met or the reason for failure. A positive value indicates successful termination, while a negative value indicates unsuccessful termination. An RC = 3 indicates the gradient vanished, that is, convergence as specified by equation (13) was met. An RC = 7 indicates convergence based on Euclidean distance. See the SAS/IML[®] 9.1 “User’s Guide” for explanations of the 20 RC values (SAS Institute Inc. 2004, page 333) and the definitions of the various termination criteria used (pages 349–356). The program creates an output file that contains the label for the observation, the parameter estimates, the value of the L_1 norm [equation (14)], a “YES” or “NO” convergence tag, and the RC from the NLPLM procedure. The length of the label variable is initialized on line 190 and can be set to any length by the user. The program prints the results dataset (line 285), and output is saved to an Excel[®] file. The file location and name are specified by the user on line 292 of the program.

S_B Recovery 4parm

This program is also designed to input required data through an Excel[®] file. The file location and name are specified by the user on line 64 of the program (see appendix B). The program checks the validity of the initial values in a “do loop” on lines 308–315. On line 70 the user can supply a descriptive project title that will print on the top of all printed output from the program. As in the first program, the amount of printed output is controlled by the options vector on line 249. Unlike the first program, this program utilizes the TC or termination criteria vector on line 254. This vector permits users to control the maximum number of iterations (first element of the vector) and the maximum number of function calls (second element of the vector). The complexity of solving three simultaneous equations sometimes necessitates increasing these values. The constraint matrix is initialized on lines 291–293. The upper bound constraint for ξ is set on line 317 and for λ on line 319. At the user’s discretion, these upper bounds can be changed. Like in the first program, the NLPLM procedure gives a RC that indicates the termination status, and an output file is generated. The length of the label variable is set on line 229. The program prints the results dataset (line 345) and the output is saved to an Excel[®] file. The file location and name are specified by the user on line 352 of the program.

Examples and Discussion

Practical examples of the S_B recovery SAS programs heretofore described are presented and discussed. The chosen cases were taken from real stands in a selective way in order to provide an overall picture of the programs' implementation and S_B flexibility. In the following examples, stand and tree variable values are expressed in the metric system.

S_B Recovery 3param

Figure 2 shows an example Excel[®] input file with variable labels in row 1. ID is stand code (character variable), BA is basal area per unit area (m^2ha^{-1}), and NT is number of trees per unit area (trees ha^{-1}). SBMEDIAN, SBMEAN, and DMIN refer, respectively, to the median, the average, and the minimum diameter (in cm) of the observed diameter distribution. IV_LAMBDA and IV_DELTA are the initial values set for the λ and the δ parameters. Consider the four observations in figure 2. Let us use this file as input into S_B Recovery 3param. The Excel[®] file output by the program is given in figure 3. As we can see, a convergent solution was obtained on all four observations, and the L_1 norm values are very small, $< 10^{-7}$ (essentially zero) for observations "S1104" and "S1606." The use of different starting values resulted in the same solutions confirming that the global minimums were obtained. Recall that we are using restricted estimation and we can see in figure 3 that the λ values for "S0204" and "S1906" are at the upper boundary constraint. This is why the L_1 norm values are slightly positive. However, they are sufficiently small as not to cause concern.

and DMIN refer, respectively, to the median, the average, and the minimum diameter (in cm) of the observed diameter distribution. IV_LAMBDA and IV_DELTA are the initial values set for the λ and the δ parameters. Consider the four observations in figure 2. Let us use this file as input into S_B Recovery 3param. The Excel[®] file output by the program is given in figure 3. As we can see, a convergent solution was obtained on all four observations, and the L_1 norm values are very small, $< 10^{-7}$ (essentially zero) for observations "S1104" and "S1606." The use of different starting values resulted in the same solutions confirming that the global minimums were obtained. Recall that we are using restricted estimation and we can see in figure 3 that the λ values for "S0204" and "S1906" are at the upper boundary constraint. This is why the L_1 norm values are slightly positive. However, they are sufficiently small as not to cause concern.

	A	B	C	D	E	F	G	H
1	ID	BA	NT	SBMEDIAN	SBMEAN	DMIN	IV_LAMBDA	IV_DELTA
2	S0204	12.395562	320	19.65	21.412500	11.12	20.84	1.2
3	S1104	15.167923	720	17.55	15.394444	4.80	23.80	1.2
4	S1606	18.009007	280	26.80	27.035714	10.64	34.36	0.9
5	S1906	12.819787	2080	7.50	8.289423	2.40	15.68	0.9

Figure 2—Input file used on S_B Recovery 3param program (see text for variable labels description).

	A	B	C	D	E	F	G	H
1	LABEL	XI	LAMBDA	GAMMA	DELTA	L1NORM	CONVERGE	RC
2	S0204	11.12	41.67000	1.36842	1.00831	0.267617	YES	3
3	S1104	4.80	16.35537	-0.44579	0.35293	1.97E-08	YES	3
4	S1606	10.64	33.85450	0.05795	0.63881	9.50E-09	YES	3
5	S1906	2.40	31.35000	2.23179	1.36216	0.094095	YES	6

Figure 3—Output file created by S_B Recovery 3param program.

Hence, there is no need to change the upper bound for λ for these two observations.

A δ value < 0.7 generally results in a bimodal shape. For observation “S1104” we have $\delta = 0.35$ and $\gamma = -0.45$ which should give a decidedly left-skewed bimodal shape, and for observation “S1606” we have $\delta = 0.64$ and $\gamma = 0.06$ which should give a slightly right-skewed bimodal shape. The observed and S_B simulated frequencies by 5-cm diameter classes are shown in figure 4. In part A, for observation “S0204,” we have a classic right-skewed unimodal graph. We see in part B (observation “S1104”) a mode at 10 cm and the second much larger mode (as expected) at 20 cm. There is a perfect pairing of the observed and simulated mode locations and the S_B curve gives a good fit to the observed mode heights. Part C of the graph displays another bimodal distribution (observation “S1606”) with predicted modes at 15 and 40 cm. The observed modes occurred at 20 and 40 cm, and though there is some disagreement, the S_B curve is a reasonable simulation. Statistical distributions such as the Weibull and lognormal cannot fit such shapes. Finally, in part D (observation “S1906”), we see a very good match between the observed and predicted reverse-J shaped distributions.

S_B Recovery 4param

Let us look at new examples using the all-parameter recovery system. We will use as input into program S_B Recovery 4param the file displayed in figure 5. The additional variable used as input, labeled SBMUPRIME3, refers to the third noncentral moment of diameter distribution. The variable IV_XI is the initial value for the ξ parameter (in our case it was set to 0.8 of observed minimum diameter). The Excel[®] file output by the program is given in figure 6. There are several things to note in the output file. Observation “S2112” had an unsuccessful termination, the RC = -8 code means maximum number of iterations exceeded. For observation “S2504” the solution for δ occurred on the lower boundary at 0.01. Figure 7 is a graph of “S2504” and illustrates that this is not a reasonable simulation. The solution for observation “S2804” looks good. Notice that the ξ value is at its lower boundary of zero but the L_1 norm is very small. The solution for observation “S0406” looks reasonable but has the largest L_1 norm value of the four solutions. This is probably due to the value of λ being at its upper bound.




Figure 4—Observed frequencies and S_B simulated distributions using the three-parameter recovery program. (A) Observation “S0204” is a classic right-skewed unimodal fit. In (B) observation “S1104” and (C) observation “S1606” we see reasonable bimodal fits to the observed frequencies. (D) observation “S1906” shows an excellent fit to the reverse-J shaped distribution.

Microsoft Excel - Four_parm_input_example.xls

	A	B	C	D	E	F	G	H	I
1	ID	BA	NT	SBMEDIAN	SBMEAN	SBMUPRIME3	IV_XI	IV_LAMBDA	IV_DELTA
2	S2112	39.398713	520	29.60	30.669231	31115.6217692	18.56	25.74	1.2
3	S2504	44.859634	1200	21.75	21.255000	11149.8915500	10.00	20.00	0.5
4	S2804	38.357857	920	22.65	22.680435	12789.9818913	3.00	35.00	2.5
5	S0406	37.391770	1900	14.90	15.408421	4284.6042105	6.72	21.58	1.8
6									

Ready

Figure 5—Input file used on S_B Recovery 4param program (see text for variable labels description).

Microsoft Excel - Four_parm_output_example.xls

	A	B	C	D	E	F	G	H
1	LABEL	XI	LAMBDA	GAMMA	DELTA	L1NORM	CONVERGE	RC
2	S2112	25.33575	11.24027	0.06782	0.13779	0.015456	NO	-8
3	S2504	16.27094	9.94624	-0.00204	0.01	0.004346	YES	3
4	S2804	0	47.33625	0.24323	2.82539	0.000732	YES	3
5	S0406	6.83758	43.16000	2.81293	1.91237	0.032907	YES	3
6								

Ready

Figure 6—Output file created by S_B Recovery 4param program.




Figure 7—Observed frequencies and S_B simulated distribution for observation “S2504” using the initial solution of the all-parameter recovery program.

Let us do another run of the program. The $\hat{\xi} = 16.27$ cm solution for observation “S2504” seems quite large so we will impose the observed plot minimum diameter of 12 cm as an upper bound. Line 318 of the program is a blank spacing line. To change the upper bound ξ constraint for observation “S2504” we add the following “IF” statement on line 318: “IF LABEL=‘S2504’ THEN UB_XI = 12.” For observations “S2112” and “S0406” we will try a different set of starting values. The updated input file is shown in figure 8. The output file from this new run is shown in figure 9. We see that this time a convergent solution was obtained on “S2112” and the L_1 norm goes to zero. The λ and δ values have substantially increased and are more in line with expectations. Figure 10A shows a good correspondence between the observed and simulated distributions. The new solution for observation “S2504” has a larger L_1 norm (due to the new ξ constraint), but compare the graph based on the old solution displayed in figure 7 with the new graph shown in figure 10B. It is obvious that the new solution, based on imposing observed minimum diameter as an upper bound constraint on ξ , gives a superior fit against the observed distribution. Concerning observation

“S2804” figure 10C indicates a close conformance between the observed and predicted distribution. For observation “S0406,” looking at the old L_1 norm value in figure 6 (≈ 0.03) and the new L_1 norm value in figure 9 (≈ 0), we see the original convergent solution was at a local minimum. The new solution is at the global minimum and is displayed in figure 10D.

As a final example, let us refit observation “S1104” using the all-parameter recovery program. The input for this observation was shown in figure 2 as input for S_B Recovery 3parm. We need to include the value for SBMUPRIME3 which is 5014.2784444. The solution is as follows: $\hat{\xi} = 6.47538$, $\hat{\lambda} = 14.68004$, $\hat{\gamma} = 0.30239$, $\hat{\delta} = 0.26946$, and the L_1 norm = 1.83×10^{-12} . The observed and simulated distributions are shown in figure 11. Compared to figure 4B, we see a much closer correspondence between observed and predicted frequencies in the 10- and 15-cm diameter classes. In this instance, the all-parameter recovery solution provides a better fit compared to the three-parameter recovery solution.

	A	B	C	D	E	F	G	H	I
1	ID	BA	NT	SBMEDIAN	SBMEAN	SBMUPRIME3	IV_XI	IV_LAMBDA	IV_DELTA
2	S2112	39.398713	520	29.60	30.669231	31115.6217692	18.56	25.74	0.8
3	S2504	44.859634	1200	21.75	21.255000	11149.8915500	10.00	20.00	0.5
4	S2804	38.357857	920	22.65	22.680435	12789.9818913	3.00	35.00	2.5
5	S0406	37.391770	1900	14.90	15.408421	4284.6042105	6.72	21.58	1
6									

Figure 8—Updated initial values used on S_B Recovery 4parm program (see text for details).

	A	B	C	D	E	F	G	H
1	LABEL	XI	LAMBDA	GAMMA	DELTA	L1NORM	CONVERGE	RC
2	S2112	24.39041	16.06021	0.36354	0.49547	3.64E-12	YES	3
3	S2504	12	16.66871	-0.18498	0.53924	0.028909	YES	3
4	S2804	0	47.33625	0.24323	2.82539	0.000732	YES	3
5	S0406	9.66245	14.40509	0.40168	0.71752	4.29E-10	YES	3
6								

Figure 9—Output file created by S_B Recovery 4parm program for the new run with updated initial values.







Figure 10—Observed frequencies and S_B simulated distributions using the updated output values of the all-parameter recovery program. All four graphs (A-D) display good fits to the observed frequencies.




Figure 11—Observed frequencies and S_B simulated distribution for observation “S1104” using the all-parameter recovery program.

Concluding Remarks

Distinct parameter estimation methods are available for the S_B distribution. Nevertheless, at the state-of-the-art, few studies have been conducted for its inclusion in stand models through a moment recovery-based approach. A major reason is that the S_B parameter recovery strategies involve solving complex systems of nonlinear equations. In this paper we presented methodology that was implemented in two SAS programs: S_B Recovery 3parm and S_B Recovery 4parm.

The programs were designed using a robust nonlinear least-squares minimization technique, the LM algorithm, and exploitation of the IML capabilities of SAS software. It is necessary to impose restrictions on the parameters to prevent projecting the parameters into an unfeasible space and/or to avoid unreasonable solutions. Restricted estimation was achieved using the Kuhn-Tucker theorem and the Lagrange function.

Instructive examples of the S_B recovery models were presented in order to illustrate their use. Users should be capable of reproducing the example runs and doing new simulations in an easy manner. SAS programs in text files are available by request from the authors.

Acknowledgments

This study was funded by the Forest Service, Southern Research Station, and Instituto Nacional de Investigação Agrária e das Pescas (under project POAgro 372). We extend special thanks to KaDonna Randolph and Bill Smith for their critical reviews and valuable suggestions.

Literature Cited

- Avriel, M. 2003. *Nonlinear programming: analysis and methods*. Mineola, NY: Dover Publications. 512 p.
- Fonseca, T.F. 2004. *Modelação do crescimento, mortalidade e distribuição diamétrica, do pinhal bravo no Vale do Tâmega*. Vila Real, Portugal: Universidade de Trás-os-Montes e Alto Douro. 248 p. Ph.D. dissertation. In Portuguese.
- Fonseca, T.F.; Marques, C.P.; Parresol, B.R. 2009. Describing maritime pine diameter distributions with Johnson's S_B distribution using a new all-parameter recovery approach. *Forest Science*. 55(4): 367–373.
- Gove, J.H.; Patil, G.P. 1998. Modeling the basal area-size distribution of forest stands: a compatible approach. *Forest Science*. 44(2): 285–297.
- Hafley, W.L.; Buford, M.A. 1985. A bivariate model for growth and yield prediction. *Forest Science*. 31(1): 237–247.
- Hafley, W.L.; Schreuder, H.T. 1977. Statistical distributions for fitting diameter and height data in even-aged stands. *Canadian Journal of Forest Research*. 7: 481–487.
- Hyink, D.M.; Moser, J.W., Jr. 1983. A generalized framework for projecting forest yield and stand structure using diameter distributions. *Forest Science*. 29(1): 85–95.
- Johnson, N.L. 1949. Systems of frequency curves generated by methods of translation. *Biometrika*. 36: 149–176.
- Johnson, N.L.; Kotz, S. 1970. *Continuous univariate distributions-1*. New York: John Wiley. 300 p.
- Kamziah, A.K.; Ahmad, M.I.; Lapongan, J. 1999. Nonlinear regression approach to estimating Johnson S_B parameters for diameter data. *Canadian Journal of Forest Research*. 29: 310–314.
- Kangas, A.; Maltamo, M. 2000. Calibrating predicted diameter distribution with additional information. *Forest Science*. 46: 390–396.
- Kiviste, A.; Nilson, A.; Hordo, M.; Merenäkk, M. 2003. Diameter distribution models and height-diameter equations for Estonian forests. In: Amaro, A.; Reed, D.; Soares, P., eds. *Modelling forest systems*. Wallingford, UK: CABI Publishing: 169–179. Chapter 15.
- Kuhn, H.W.; Tucker, A.W. 1951. Nonlinear programming. In: *Proceedings, 2^d Berkeley symposium on mathematical statistics and probability*. Berkeley, CA: University of California Press: 481–492.
- Lopes, S. 2001. *Modelação matemática da distribuição de diâmetros em povoamentos de pinheiro bravo*. Coimbra, Portugal: Universidade de Coimbra. 102 p. M.S. thesis. In Portuguese.

- Newbury, J.D.; Burk, T.E. 1985. S_B distribution-based models for individual tree merchantable volume-total volume ratio. *Forest Science*. 31: 389–398.
- Parresol, B.R. 1983. Modeling diameter distributions in southern pine plantations. SP-83-075. Baton Rouge, LA: Louisiana State University. 49 p. Masters of Applied Statistics special problem.
- Parresol, B.R. 2003. Recovering parameters of Johnson's S_B distribution. Res. Pap. SRS-31. Asheville, NC: U.S. Department of Agriculture Forest Service, Southern Research Station. 9 p.
- Ralston, A.; Rabinowitz, P. 1978. *A first course in numerical analysis*. 2^d ed. New York: McGraw-Hill. 556 p.
- Ranganathan, A. 2004. The Levenberg-Marquardt algorithm. <http://www.cc.gatech.edu/~ananth/docs/lmtut.pdf>. [Date accessed: June 22, 2009].
- SAS Institute Inc. 2004. SAS/IML[®] 9.1 user's guide. Cary, NC: SAS Institute Inc. 1,040 p.
- Scolforo, J.R.S.; Thierschi, A. 1998. Estimativas e testes da distribuição de frequência diâétrica para *Eucalyptus camaldulensis*, através da distribuição S_B , por diferentes métodos de ajuste. *Scientia Forestalis*. 54: 93–106. In Portuguese.
- Tham, Á. 1988. Estimate and test frequency distributions with the Johnson S_B function from stand parameters in young mixed stands after different thinning treatments. In: Ek, A.R.; Shifley, S.R.; Burk, T.E., eds. *Forest growth modelling and prediction*. Proceedings of the IUFRO conference. Gen. Tech. Rep. NC-120. St. Paul, MN: U.S. Department of Agriculture Forest Service, North Central Forest Experiment Station: 255–262. Vol. 1.
- Von Gadow, K. 1983. Fitting distributions in *Pinus patula* stands. *Suid-Afrikaanse Bosbouydskrif*. 126: 20–29.
- Zhou, B.; McTague, J.P. 1996. Comparison and evaluation of five methods of estimation of the Johnson system of parameters. *Canadian Journal of Forest Research*. 26: 928–935.

Appendix A

SAS Source Code for S_B Recovery 3parm

(Note: Line numbers are for reference and are not part of the program.)

```

1  /*******
2  /*
3  /*          PROGRAM SB RECOVERY 3PARAM (SAS version 9.1)
4  /*
5  /*  DESIGNED FOR TREE DIAMETER DISTRIBUTIONS, THIS PROGRAM USES A
6  /*  PERCENTILE-MOMENT METHOD TO RECOVER THE RANGE PARAMETER
7  /*  (LAMBDA) AND BOTH SHAPE PARAMETERS (GAMMA, DELTA) OF JOHNSON'S
8  /*  SB DISTRIBUTION. THE LOCATION PARAMETER (XI) AND INITIAL
9  /*  VALUES FOR LAMBDA AND DELTA MUST BE SUPPLIED TO START THE
10 /*  ITERATIVE LEVENBERG-MARQUARDT PROCEDURE.
11 /*
12 /*  INPUT VARIABLES:
13 /*
14 /*  ID = IDENTIFICATION CHARACTER VARIABLE FOR LABELING PURPOSES
15 /*  BA = STAND BASAL AREA PER UNIT AREA
16 /*  NT = NUMBER OF TREES PER UNIT AREA
17 /*  SBMEDIAN = MEDIAN DIAMETER
18 /*  SBMEAN   = AVERAGE DIAMETER
19 /*  DMIN    = MINIMUM DIAMETER, RECODED AS XI IN THE PROGRAM
20 /*  IV_LAMBDA = INITIAL OR STARTING VALUE FOR LAMBDA
21 /*  IV_DELTA = INITIAL OR STARTING VALUE FOR DELTA
22 /*
23 /*  OUTPUT VARIABLES:
24 /*
25 /*  LABEL = IDENTIFICATION CHARACTER VARIABLE
26 /*  XI    = LOCATION PARAMETER
27 /*  LAMBDA = RANGE PARAMETER
28 /*  GAMMA = SHAPE PARAMETER RELATED TO SKEWNESS
29 /*  DELTA = SHAPE PARAMETER
30 /*  L1_NORM = VALUE OF L1 NORM OF THE MINIMIZED FUNCTIONS
31 /*  CONVERGE = 'YES' OR 'NO' CHARACTER VARIABLE FOR CONVERGENCE
32 /*  RC = SAS RETURN CODE FROM IML ROUTINE NLPLM INDICATING WHICH
33 /*      CONVERGENCE CRITERIA WAS MET OR REASON FOR NONCONVERGENCE
34 /*
35 /*  Reference: Parresol, B.R. 2003. Recovering parameters of
36 /*            Johnson's SB distribution. USDA Forest Service
37 /*            Research Paper SRS-31. 9 p.
38 /*
39 /*  Programmed by Bernard R. Parresol
40 /*            USDA Forest Service
41 /*            Southern Research Station
42 /*            200 WT weaver Boulevard
43 /*            Asheville, NC 28804 USA
44 /*
45  /*******
46
47  OPTIONS NODATE SOURCE;
48
49  *----- READ DATA FROM AN EXCEL FILE;
50  *----- USER SUPPLIED DATAFILE IN PROC IMPORT;
51
52  PROC IMPORT OUT= WORK.ONE
53             DATAFILE= "filename"
54             DBMS=EXCEL REPLACE;
55             GETNAMES=YES;
56  RUN;
57
58  TITLE '3 PARAMETER RECOVERY SYSTEM FOR SB DISTRIBUTION';
59  * TITLE2 '-xxxxxxxxx-'; /* <== USER CAN ADD DESCRIPTIVE PROJECT TITLE */
60

```

```

61 PROC IML; /* START MATRIX LANGUAGE */
62
63 START FCN(X)
64 GLOBAL(K,C,i,BA,NT,SBMEDIAN,SBMEAN,XI,LAMBDA,DELTA,GAMMA,R,DM1,DM2,F);
65
66 /*****
67 /*
68 /*     MODULE FCN IS CALLED BY PROCEDURE NLPLM TO
69 /*     EVALUATE THE LEFT-HAND SIDE OF EQUATIONS:
70 /*         FCN(LAMBDA,DELTA) - SBMEAN = 0
71 /*         FCN(LAMBDA,DELTA) - BA     = 0
72 /*
73 /*****
74
75 *----- SOLVE FOR GAMMA GIVEN ESTIMATES OF XI, LAMBDA, AND DELTA;
76
77     LAMBDA = X[1];
78     DELTA  = X[2];
79     GAMMA  = DELTA*LOG(LAMBDA/(SBMEDIAN[i]-XI)-1);
80
81 *----- OBTAIN MOMENTS OF SB DISTRIBUTION;
82
83     A = {.M .P}; /* LIMITS OF INTEGRATION */
84     R = 1; /* EXPONENT FOR 1ST MOMENT */
85     CALL QUAD(DM,"MOMENT",A) /* NUMERICAL INTEGRATION */
86     EPS=1E-10;
87     DM1 = C*DM; /* VALUE OF FIRST MOMENT */
88
89     R = 2; /* EXPONENT FOR 2ND MOMENT */
90     CALL QUAD(DM,"MOMENT",A) /* NUMERICAL INTEGRATION */
91     EPS=1E-10;
92     DM2 = C*DM; /* VALUE OF SECOND MOMENT */
93
94 *----- COMPUTE VALUES OF FCN;
95
96     F = {0 0};
97     F[1] = XI + LAMBDA*DM1 - SBMEAN[i];
98     F[2] = (XI**2 + 2*XI*LAMBDA*DM1 + LAMBDA**2*DM2)*K*NT[i] - BA[i];
99     RETURN(F);
100 FINISH FCN;
101
102
103 START MOMENT(Z) GLOBAL(DELTA,GAMMA,R);
104
105 /*****
106 /*
107 /*     MODULE MOMENT IS FOR EVALUATING THE
108 /*     MOMENTS OF THE SB DISTRIBUTION.
109 /*
110 /*****
111
112     V = EXP(-.5*Z**2)/(1 + EXP((GAMMA-Z)/DELTA))**R;
113     RETURN(V);
114 FINISH MOMENT;
115
116

```

```

117 START PSEUDO(Z) GLOBAL(DELTA,GAMMA,R);
118
119 /*****
120 /*
121 /*  MODULE PSEUDO IS FOR EVALUATING THE
122 /*  PSEUDO-MOMENTS OF THE SB DISTRIBUTION.
123 /*
124 /*****
125
126 V = Z*EXP(-.5*Z**2)/(1 + EXP((GAMMA-Z)/DELTA))**R;
127 RETURN(V);
128 FINISH PSEUDO;
129
130
131 START DERIV(X) GLOBAL(K,C,i,XI,LAMBDA,GAMMA,DELTA,R,DM1,DM2,SBMEDIAN,NT);
132
133 /*****
134 /*
135 /*  MODULE DERIV IS CALLED BY NLPLM
136 /*  TO EVALUATE THE PARTIAL DERIVATIVES OF
137 /*      FCN(LAMBDA,DELTA) = SBMEAN
138 /*      FCN(LAMBDA,DELTA) = BA
139 /*
140 /*****
141
142 *-----  OBTAIN THIRD MOMENT;
143
144 A = {.M .P};
145 R = 3;
146 CALL QUAD(DM,"MOMENT",A)
147 EPS=1E-10 PEAK=1 SCALE=0.1;
148 DM3 = C*DM;
149
150 *-----  OBTAIN PSEUDO-MOMENTS;
151
152 R = 1;
153 CALL QUAD(PM,"PSEUDO",A)
154 EPS=1E-10 PEAK=1 SCALE=0.1;
155 PM1 = C*PM;
156
157 R = 2;
158 CALL QUAD(PM,"PSEUDO",A)
159 EPS=1E-10 PEAK=1 SCALE=0.1;
160 PM2 = C*PM;
161
162 R = 3;
163 CALL QUAD(PM,"PSEUDO",A)
164 EPS=1E-10 PEAK=1 SCALE=0.1;
165 PM3 = C*PM;
166
167 *-----  DEFINE COMMON ELEMENTS OF DERIVATIVES;
168
169 DM2_1 = DM2 - DM1;
170 DM3_2 = DM3 - DM2;
171 PM2_1 = PM2 - PM1;
172 PM3_2 = PM3 - PM2;
173 DN = LAMBDA - SBMEDIAN[i] + XI;
174
175 *-----  COMPUTE JACOBIAN MATRIX;
176

```



```

177         J = J(2,2,0);
178         J[1,1] = DM1 + LAMBDA * DM2_1 / DN; /* f1/LAMBDA */
179         J[1,2] = LAMBDA*PM2_1 / (DELTA*DELTA); /* f1/DELTA */
180         J[2,1] = (XI*DM1 + LAMBDA*DM2 + (XI*LAMBDA
181                 *DM2_1 + LAMBDA**2*DM3_2) / DN)*2*K*NT[i]; /* f2/LAMBDA */
182         J[2,2] = LAMBDA/DELTA**2*(XI*PM2_1 + LAMBDA*PM3_2)
183                 *2*K*NT[i]; /* f2/DELTA */
184         RETURN (J);
185 FINISH DERIV;
186
187
188 ***** <-----> EXECUTE PROGRAM <----- *****;
189
190 LABEL = '12345'; /* TO LABEL OUTPUT, LENGTH CAN BE SET BY USER */
191 CONVERGE = '123'; /* INITIALIZE CHARACTER VARIABLE OF LENGTH 3 */
192
193 *----- SET UP OUTPUT DATASET TO HOLD PARAMETER ESTIMATES AND RESULTS;
194
195 CREATE RESULTS VAR {LABEL XI LAMBDA GAMMA DELTA L1_NORM CONVERGE RC};
196
197 USE ONE; /* INPUT DATASET USED BY PROC IML */
198 READ ALL VAR{ID BA NT SBMEDIAN SBMEAN DMIN IV_LAMBDA IV_DELTA};
199
200 NOBS = NROW(BA); /* NUMBER OF OBSERVATIONS */
201 IV = IV_LAMBDA||IV_DELTA; /* MATRIX CONTAINING INITIAL VALUES */
202
203 *----- INITIALIZATION;
204
205 PI = 4*ATAN(1);
206 *--K = PI/576; /* CONVERSION TO ft2 - USE FOR ENGLISH SYSTEM */
207 K = PI/40000; /* CONVERSION TO m2 - USE FOR METRIC SYSTEM */
208 C = 1/SQRT(2*PI); /* CONSTANT FOR MOMENTS */
209
210 OPTN = {2 1}; /* OPTIONS VECTOR */
211 /* 1ST VALUE IS NUMBER OF EQUATIONS IN SYSTEM */
212 /* 2ND VALUE DETERMINES AMOUNT OF PRINTED OUTPUT */
213 /* 0=NO OUTPUT, 1=SUMMARIES & ITERATION HISTORY */
214
215
216 /*--- BOUNDARY CONDITIONS ARE IMPOSED WITH THE CON OR CONSTRAINTS ---*/
217 /*--- MATRIX. CONSTRAINTS MUST USE >= AND <= INEQUALITIES, NOT > OR < ---*/
218 /*--- INEQUALITIES. WITH THIS IN MIND, WE USE THE FOLLOWING FACTS TO ---*/
219 /*--- CONSTRUCT THE NECESSARY CON MATRIX. GAMMA (G) IS A FUNCTION OF ---*/
220 /*--- THE OTHER 3 PARAMETERS XI, LAMBDA(L) AND DELTA (D) PLUS THE ---*/
221 /*--- MEDIAN DIAMETER (SBMEDIAN), i.e. G = D*LN(L/(SBMEDIAN-XI)-1). ---*/
222 /*--- THE EQUATION REVEALS THAT L/(SBMEDIAN-XI) > 1 TO AVOID AN ---*/
223 /*--- ILLEGAL LOG ARGUMENT, THUS SBMEDIAN-XI < L. AS A PRACTICAL ---*/
224 /*--- MATTER THE RANGE SHOULD BE RESTRICTED. A REASONABLE UPPER BOUND ---*/
225 /*--- IS 2xINITIAL GUESS FOR L. BY DEFINITION OF THE SB DISTRIBUTION, ---*/
226 /*--- D > 0. GATHERING ALL THIS TOGETHER, WE HAVE: ---*/
227 /*---
228 /*--- SBMEDIAN-XI < L <= 2 x IV_L (IV IS INITIAL VALUE) ---*/
229 /*--- 0 < D ---*/
230 /*---
231 /*--- BECAUSE CONSTRAINTS MUST BE EXPRESSED AS <= OR >=, WE NEED TO ---*/
232 /*--- MAKE SMALL ADJUSTMENTS. OUR FINAL CONSTRAINTS ARE: ---*/
233 /*---
234 /*--- SBMEDIAN-XI+0.01 <= L <= 2 x IV_L ---*/
235 /*--- 0.01 <= D ---*/
236

```

```

237
238   CON = {0 1E-2, 100 .}; /* INITIALIZE PARAMETER CONSTRAINTS MATRIX */
239                           /* ELEMENTS OF ROW 1 ARE LOWER BOUNDS FOR */
240                           /* LAMBDA & DELTA. ELEMENTS OF ROW 2 ARE */
241                           /* UPPER BOUNDS FOR LAMBDA & DELTA. A '.' */
242                           /* OR MISSING VALUE MEANS NO BOUNDARY. */
243
244 *-----   PROCESS OBSERVATIONS;
245
246 DO i = 1 TO NOBS;          /* LOOP THROUGH OBSERVATIONS */
247
248   LABEL = ID[i];
249   XI=DMIN[i];
250   X=IV[i,];                /* INITIAL VALUES VECTOR FOR PARAMETERS */
251
252 *-----   CHECK VALIDITY OF INITIAL VALUES;
253
254   IF X[1] < SBMEDIAN[i]-XI+0.01 | X[2] < 0.01 THEN DO;
255     LAMBDA = X[1];
256     DELTA = X[2];
257     PRINT "ERROR - INITIAL VALUES ARE INVALID:" LABEL XI LAMBDA DELTA;
258     GOTO CONTINUE;
259   END;
260
261   LB=SBMEDIAN[i]-XI+0.01; /* LOWER BOUNDARY CONSTRAINT FOR LAMBDA */
262
263   UB=2*IV[i,1];          /* UPPER BOUNDARY CONSTRAINT FOR LAMBDA */
264                           /* SET AT 2 X INITIAL GUESS FOR LAMBDA */
265                           /* USER CAN SET A DIFFERENT UPPER BOUND */
266
267   CON[1,1] = LB;         /* RESET VALUE IN CONSTRAINTS MATRIX */
268   CON[2,1] = UB;         /* RESET VALUE IN CONSTRAINTS MATRIX */
269
270   CALL NLPLM(RC,XR,"FCN",X,OPTN,CON,,,,,"DERIV"); /* LEVENBERG-MARQUARDT */
271
272   L1_NORM = SUM(ABS(F)); /* L1 NORM */
273   IF RC>0 THEN CONVERGE='YES'; ELSE CONVERGE='NO'; /* RC IS RETURN CODE */
274                                               /* FROM NLPLM */
275
276   PRINT LABEL XI LAMBDA GAMMA DELTA L1_NORM;
277   APPEND; /* ADD OBSERVATIONS TO OUTPUT DATASET */
278   CONTINUE; /* GO TO NEXT OBSERVATION */
279 END; /* END OF DO LOOP PROCESSING */
280
281 QUIT; /* EXIT IML */
282
283 *-----   PRINT RESULTS;
284
285 PROC PRINT DATA=RESULTS;
286 RUN;
287
288 *-----   SAVE RESULTS TO AN EXCEL FILE;
289 *-----   USER SUPPLIED OUTFILE IN PROC EXPORT;
290
291 PROC EXPORT DATA= WORK.RESULTS
292             OUTFILE= "filename"
293             DBMS=EXCEL REPLACE;
294 RUN;

```

Appendix B

SAS Source Code for S_B Recovery 4parm

(Note: Line numbers are for reference and are not part of the program.)

```

1 /*****
2 /*
3 /*          PROGRAM SB RECOVERY 4PARAM (SAS version 9.1)
4 /*
5 /*  DESIGNED FOR TREE DIAMETER DISTRIBUTIONS, THIS PROGRAM USES A
6 /*  PERCENTILE-MOMENT METHOD TO RECOVER ALL FOUR PARAMETERS OF
7 /*  JOHNSON'S SB DISTRIBUTION: LOCATION PARAMETER (XI), RANGE
8 /*  PARAMETER (LAMBDA) AND BOTH SHAPE PARAMETERS (GAMMA, DELTA).
9 /*  INITIAL VALUES FOR XI, LAMBDA, AND DELTA MUST BE SUPPLIED TO
10 /*  START THE ITERATIVE LEVENBERG-MARQUARDT PROCEDURE.
11 /*
12 /*  INPUT VARIABLES:
13 /*
14 /*  ID = IDENTIFICATION CHARACTER VARIABLE FOR LABELING PURPOSES
15 /*  BA = STAND BASAL AREA PER UNIT AREA
16 /*  NT = NUMBER OF TREES PER UNIT AREA
17 /*  SBMEDIAN  = MEDIAN DIAMETER
18 /*  SBMEAN    = AVERAGE DIAMETER
19 /*  SBMUPRIME3 = THIRD NONCENTRAL MOMENT
20 /*  IV_XI     = INITIAL OR STARTING VALUE FOR XI
21 /*  IV_LAMBDA = INITIAL OR STARTING VALUE FOR LAMBDA
22 /*  IV_DELTA  = INITIAL OR STARTING VALUE FOR DELTA
23 /*
24 /*  OUTPUT VARIABLES:
25 /*
26 /*  LABEL = IDENTIFICATION CHARACTER VARIABLE
27 /*  XI    = LOCATION PARAMETER
28 /*  LAMBDA = RANGE PARAMETER
29 /*  GAMMA = SHAPE PARAMETER RELATED TO SKEWNESS
30 /*  DELTA = SHAPE PARAMETER
31 /*  L1_NORM = VALUE OF L1 NORM OF THE MINIMIZED FUNCTIONS
32 /*  CONVERGE = 'YES' OR 'NO' CHARACTER VARIABLE FOR CONVERGENCE
33 /*  RC = SAS RETURN CODE FROM IML ROUTINE NLPLM INDICATING WHICH
34 /*      CONVERGENCE CRITERIA WAS MET OR REASON FOR NONCONVERGENCE
35 /*
36 /*  Reference:  Fonseca, T.F., Marques, C.P., and Parresol, B.R.
37 /*              2009. Describing maritime pine diameter
38 /*              distributions with Johnson's SB distribution
39 /*              using a new all-parameter recovery approach.
40 /*              Forest Science. 55(4): 367-373.
41 /*
42 /*  Programmed by Bernard R. Parresol
43 /*              USDA Forest Service
44 /*              Southern Research Station
45 /*              200 WT Weaver Boulevard
46 /*              Asheville, NC 28804 USA
47 /*
48 /*              AND
49 /*
50 /*              Teresa Fidalgo Fonseca
51 /*              Departamento de Ciências Florestais
52 /*              e Arquitetura Paisagista
53 /*              Universidade de Trás-os-Montes e Alto Douro
54 /*              Apartado 1013, 5001-801 Vila Real, Portugal
55 /*
56 /*****
57
58 OPTIONS NODATE SOURCE;
59
60 *----- READ DATA FROM AN EXCEL FILE;
61 *----- USER SUPPLIED DATAFILE IN PROC IMPORT;

```

```

62
63 PROC IMPORT OUT= WORK.ONE
64         DATAFILE= "filename"
65         DBMS=EXCEL REPLACE;
66     GETNAMES=YES;
67 RUN;
68
69 TITLE 'ALL PARAMETER RECOVERY SYSTEM FOR SB DISTRIBUTION';
70 * TITLE2 '-xxxxxxxxx-'; /* <== USER CAN ADD DESCRIPTIVE PROJECT TITLE */
71
72 PROC IML; /* START MATRIX LANGUAGE */
73
74 START FCN(X)
75 GLOBAL(K,C,i,BA,NT,SBMEDIAN,SBMEAN,SBMUPRIME3,
76         XI,LAMBDA,DELTA,GAMMA,R,DM1,DM2,DM3,F);
77
78 /*****
79 */
80 /*     MODULE FCN IS CALLED BY PROCEDURE NLPLM TO
81 /*     EVALUATE THE LEFT-HAND SIDE OF EQUATIONS:
82 /*         FCN(XI,LAMBDA,DELTA) - SBMEAN = 0
83 /*         FCN(XI,LAMBDA,DELTA) - BA     = 0
84 /*         FCN(XI,LAMBDA,DELTA) - SBSIZE = 0
85 */
86 /*****
87
88 *----- SOLVE FOR GAMMA GIVEN ESTIMATES OF XI, LAMBDA, AND DELTA;
89
90     XI     = X[1];
91     LAMBDA = X[2];
92     DELTA  = X[3];
93     GAMMA  = DELTA*LOG(LAMBDA/(SBMEDIAN[i]-XI)-1);
94
95 *----- OBTAIN MOMENTS OF SB DISTRIBUTION;
96
97     A = {.M .P}; /* LIMITS OF INTEGRATION */
98     R = 1; /* EXPONENT FOR 1ST MOMENT */
99     CALL QUAD(DM,"MOMENT",A) /* NUMERICAL INTEGRATION */
100     EPS=1E-10;
101     DM1 = C*DM; /* VALUE OF FIRST MOMENT */
102
103     R = 2; /* EXPONENT FOR 2ND MOMENT */
104     CALL QUAD(DM,"MOMENT",A) /* NUMERICAL INTEGRATION */
105     EPS=1E-10;
106     DM2 = C*DM; /* VALUE OF SECOND MOMENT */
107
108     R = 3; /* EXPONENT FOR 3RD MOMENT */
109     CALL QUAD(DM,"MOMENT",A) /* NUMERICAL INTEGRATION */
110     EPS=1E-10 PEAK=1 SCALE=0.1;
111     DM3 = C*DM; /* VALUE OF THIRD MOMENT */
112
113 *----- COMPUTE VALUES OF FCN;
114
115     F = {0 0 0};
116     F[1] = XI + LAMBDA*DM1 - SBMEAN[i];
117     F[2] = (XI**2 + 2*XI*LAMBDA*DM1 + LAMBDA**2*DM2)*K*NT[i] - BA[i];
118     F[3] = XI**3 + 3*XI**2*LAMBDA*DM1 + 3*XI*LAMBDA**2*DM2 + LAMBDA**3*DM3
119           - SBMUPRIME3[i];
120     RETURN(F);
121 FINISH FCN;

```

```

122
123
124 START MOMENT(Z) GLOBAL(DELTA,GAMMA,R);
125
126 /*****
127 /*
128 /*    MODULE MOMENT IS FOR EVALUATING THE
129 /*    MOMENTS OF THE SB DISTRIBUTION.
130 /*
131 /*****
132
133     V = EXP(-.5*Z**2)/(1 + EXP((GAMMA-Z)/DELTA))**R;
134     RETURN(V);
135 FINISH MOMENT;
136
137
138 START PSEUDO(Z) GLOBAL(DELTA,GAMMA,R);
139
140 /*****
141 /*
142 /*    MODULE PSEUDO IS FOR EVALUATING THE
143 /*    PSEUDO-MOMENTS OF THE SB DISTRIBUTION.
144 /*
145 /*****
146
147     V = Z*EXP(-.5*Z**2)/(1 + EXP((GAMMA-Z)/DELTA))**R;
148     RETURN(V);
149 FINISH PSEUDO;
150
151
152 START DERIV(X) GLOBAL(K,C,i,XI,LAMBDA,GAMMA,DELTA,R,DM1,DM2,DM3,SBMEDIAN,NT);
153
154 /*****
155 /*
156 /*    MODULE DERIV IS CALLED BY NLPLM
157 /*    TO EVALUATE THE PARTIAL DERIVATIVES OF
158 /*    FCN(XI,LAMBDA,DELTA) = SBMEAN
159 /*    FCN(XI,LAMBDA,DELTA) = BA
160 /*    FCN(XI,LAMBDA,DELTA) = SBSIZE
161 /*
162 /*****
163
164 *----- OBTAIN FOURTH MOMENT;
165
166     A = {.M .P};
167     R = 4;
168     CALL QUAD(DM,"MOMENT",A)
169     EPS=1E-10 PEAK=1 SCALE=0.1;
170     DM4 = C*DM;
171
172 *----- OBTAIN PSEUDO-MOMENTS;
173
174     R = 1;
175     CALL QUAD(PM,"PSEUDO",A)
176     EPS=1E-10 PEAK=1 SCALE=0.1;
177     PM1 = C*PM;
178

```

```

179      R = 2;                                /* EXPONENT FOR 2ND PSEUDO-MOMENT */
180      CALL QUAD(PM,"PSEUDO",A)              /* NUMERICAL INTEGRATION          */
181      EPS=1E-10 PEAK=1 SCALE=0.1;
182      PM2 = C*PM;                            /* VALUE OF SECOND PSEUDO-MOMENT */
183
184      R = 3;                                /* EXPONENT FOR 3RD PSEUDO-MOMENT */
185      CALL QUAD(PM,"PSEUDO",A)              /* NUMERICAL INTEGRATION          */
186      EPS=1E-10 PEAK=1 SCALE=0.1;
187      PM3 = C*PM;                            /* VALUE OF THIRD PSEUDO-MOMENT  */
188
189      R = 4;                                /* EXPONENT FOR 4TH PSEUDO-MOMENT */
190      CALL QUAD(PM,"PSEUDO",A)              /* NUMERICAL INTEGRATION          */
191      EPS=1E-10 PEAK=1 SCALE=0.1;
192      PM4 = C*PM;                            /* VALUE OF FOURTH PSEUDO-MOMENT */
193
194 *----- DEFINE COMMON ELEMENTS OF DERIVATIVES;
195
196      DM2_1 = DM2 - DM1;
197      DM3_2 = DM3 - DM2;
198      DM4_3 = DM4 - DM3;
199      DN1 = LAMBDA - SBMEDIAN[i] + XI;
200      DN2 = SBMEDIAN[i] - XI;
201
202 *----- COMPUTE JACOBIAN MATRIX;
203
204      J = J(3,3,0);
205      J[1,1] = 1 + LAMBDA**2 * DM2_1 / (DN1 * DN2);          /* f1/XI      */
206      J[1,2] = DM1 + LAMBDA * DM2_1 / DN1;                  /* f1/LAMBDA */
207      J[1,3] = LAMBDA/DELTA**2*(PM2 - PM1);                  /* f1/DELTA  */
208      J[2,1] = (XI+LAMBDA*DM1+(XI*LAMBDA**2*DM2_1+LAMBDA**3
209              *DM3_2) / (DN1 * DN2))*2*K*NT[i];            /* f2/XI      */
210      J[2,2] = (XI*DM1+LAMBDA*DM2+(XI*LAMBDA*DM2_1+LAMBDA**2
211              *DM3_2) / DN1)*2*K*NT[i];                      /* f2/LAMBDA */
212      J[2,3] = LAMBDA/DELTA**2*(XI*(PM2 - PM1) + LAMBDA
213              *(PM3 - PM2))*2*K*NT[i];                      /* f2/DELTA  */
214      J[3,1] = 3*(XI**2+2*XI*LAMBDA*DM1+LAMBDA**2*DM2+(XI**2
215              *LAMBDA**2*DM2_1+2*XI*LAMBDA**3*DM3_2
216              +LAMBDA**4*DM4_3) / (DN1 * DN2));            /* f3/XI      */
217      J[3,2] = 3*(XI**2*DM1+2*XI*LAMBDA*DM2+LAMBDA**2*DM3
218              +(XI**2*LAMBDA*DM2_1+2*XI*LAMBDA**2*DM3_2
219              +LAMBDA**3*DM4_3) / DN1);                      /* f3/LAMBDA */
220      J[3,3] = 3*LAMBDA/DELTA**2*(XI**2*(PM2 - PM1)
221              +2*XI*LAMBDA*(PM3 - PM2)
222              +LAMBDA**2*(PM4 - PM3));                      /* f3/DELTA  */
223      RETURN(J);
224 FINISH DERIV;
225
226
227 ***** -----> EXECUTE PROGRAM <----- *****;
228
229 LABEL = '12345';          /* TO LABEL OUTPUT, LENGTH CAN BE SET BY USER */
230 CONVERGE = '123';        /* INITIALIZE CHARACTER VARIABLE OF LENGTH 3  */
231
232 *----- SET UP OUTPUT DATASET TO HOLD PARAMETER ESTIMATES AND RESULTS;
233
234 CREATE RESULTS VAR {LABEL XI LAMBDA GAMMA DELTA L1_NORM CONVERGE RC};
235
236 USE ONE;                  /* INPUT DATASET USED BY PROC IML */
237 READ ALL VAR{ID BA NT SBMEDIAN SBMEAN SBMUPRIME3 IV_XI IV_LAMBDA IV_DELTA};
238

```

```

239 NOBS = NROW(BA);          /* NUMBER OF OBSERVATIONS */
240 IV = IV_XI||IV_LAMBDA||IV_DELTA; /* MATRIX CONTAINING INITIAL VALUES */
241
242 *-----  INITIALIZATION;
243
244   PI = 4*ATAN(1);
245 *--K = PI/576;          /* CONVERSION TO ft2 - USE FOR ENGLISH SYSTEM */
246   K = PI/40000;        /* CONVERSION TO m2 - USE FOR METRIC SYSTEM */
247   C = 1/SQRT(2*PI);    /* CONSTANT FOR MOMENTS */
248
249   OPTN = {3 1};        /* OPTIONS VECTOR */
250                       /* 1ST VALUE IS NUMBER OF EQUATIONS IN SYSTEM */
251                       /* 2ND VALUE DETERMINES AMOUNT OF PRINTED OUTPUT */
252                       /* 0=NO OUTPUT, 1=SUMMARIES & ITERATION HISTORY */
253
254   TC = {400 1000};     /* TERMINATION CRITERIA VECTOR */
255                       /* 1ST VALUE IS MAX ITERATIONS */
256                       /* 2ND VALUE IS MAX FUNCTION CALLS */
257
258
259 /*---  BOUNDARY CONDITIONS AND LINEAR RESTRICTIONS ARE IMPOSED WITH  ---*/
260 /*---  THE BLC MATRIX OR BOUNDARY & LINEAR CONSTRAINTS MATRIX.  ---*/
261 /*---  CONSTRAINTS MUST USE >= AND <= INEQUALITIES, NOT > OR <  ---*/
262 /*---  INEQUALITIES. WITH THIS IN MIND, WE USE THE FOLLOWING FACTS TO  ---*/
263 /*---  CONSTRUCT THE NECESSARY BLC MATRIX. GAMMA (G) IS A FUNCTION OF  ---*/
264 /*---  THE OTHER 3 PARAMETERS XI, LAMBDA(L) AND DELTA (D) PLUS THE  ---*/
265 /*---  MEDIAN DIAMETER (SBMEDIAN), i.e. G = DxLN(L/(SBMEDIAN-XI)-1).  ---*/
266 /*---  DIAMETER CAN NOT BE LESS THAN ZERO. FROM THE EQUATION IT IS  ---*/
267 /*---  OBVIOUS THAT XI MUST BE LESS THAN SBMEDIAN TO AVOID AN ILLEGAL  ---*/
268 /*---  LOG ARGUMENT, HENCE 0<=XI<SBMEDIAN. ALTERNATIVELY, ONE CAN USE  ---*/
269 /*---  OBSERVED MINIMUM DIAMETER AS AN UPPER BOUND CONSTRAINT FOR XI.  ---*/
270 /*---  THE EQUATION ALSO REVEALS THAT L/(SBMEDIAN-XI) > 1 TO AVOID AN  ---*/
271 /*---  ILLEGAL LOG ARGUMENT, THUS SBMEDIAN-XI < L. BECAUSE XI AND L  ---*/
272 /*---  ARE SIMULTANEOUSLY ESTIMATED, THIS GIVES THE LINEAR RESTRICTION  ---*/
273 /*---  XI + L > SBMEDIAN. AS A PRACTICAL MATTER THE RANGE SHOULD BE  ---*/
274 /*---  RESTRICTED. A REASONABLE UPPER BOUND IS 2xINITIAL GUESS FOR L.  ---*/
275 /*---  BY DEFINITION, D > 0. GATHERING ALL THIS TOGETHER, WE HAVE:  ---*/
276 /*---
277 /*---          0 <= XI < SBMEDIAN
278 /*---          L <= 2 x IV_L   (IV IS INITIAL VALUE)
279 /*---          0 < D
280 /*---          XI + L > SBMEDIAN
281 /*---
282 /*---  BECAUSE CONSTRAINTS MUST BE EXPRESSED AS <= OR >=, WE NEED TO  ---*/
283 /*---  MAKE SMALL ADJUSTMENTS. OUR FINAL CONSTRAINTS ARE:  ---*/
284 /*---
285 /*---          0 <= XI <= SBMEDIAN - 0.01
286 /*---          L <= 2 x IV_L
287 /*---          0.01 <= D
288 /*---          XI + L >= SBMEDIAN + 0.01
289 /*---
290
291   BLC = {0 . 1E-2 . . , /* BLC MATRIX, ELEMENTS OF ROW 1 ARE LOWER */
292          . . . . . ; /* BOUNDS FOR XI, LAMBDA & DELTA. ELEMENTS */
293          1 1 . 1 . }; /* OF ROW 2 ARE UPPER BOUNDS FOR XI, */
294                       /* LAMBDA, DELTA. ELEMENTS OF ROW 3 ARE */
295                       /* USED FOR THE LINEAR RESTRICTION. A '.' */
296                       /* OR MISSING VALUE MEANS NO BOUNDARY OR */
297                       /* IS A PLACE HOLDER. */

```



```

298
299 *----- PROCESS OBSERVATIONS;
300
301 DO i = 1 TO NOBS;          /* LOOP THROUGH OBSERVATIONS */
302
303 LABEL = ID[i];
304 X=IV[i,];                /* INITIAL VALUES VECTOR FOR PARAMETERS */
305
306 *----- CHECK VALIDITY OF INITIAL VALUES;
307
308 IF X[1] < 0 | X[1] > SBMEDIAN[i]-0.01 | X[2] < SBMEDIAN[i]-X[1]+0.01
309 | X[3] < 0.01 THEN DO;
310 XI = X[1];
311 LAMBDA = X[2];
312 DELTA = X[3];
313 PRINT "ERROR - INITIAL VALUES ARE INVALID:" LABEL XI LAMBDA DELTA;
314 GOTO CONTINUE;
315 END;
316
317 UB_XI = SBMEDIAN[i]-0.01; /* UPPER BOUNDARY CONSTRAINT FOR XI */
318
319 UB_LAMBDA = 2*IV[i,2];    /* UPPER BOUNDARY CONSTRAINT FOR LAMBDA */
320 /* SET AT 2 x INITIAL GUESS FOR LAMBDA */
321 /* USER CAN SET A DIFFERENT UPPER BOUND */
322
323 LR = SBMEDIAN[i]+0.01;   /* LINEAR RESTRICTION */
324
325 BLC[2,1] = UB_XI;        /* RESET VALUE IN CONSTRAINTS MATRIX */
326 BLC[2,2] = UB_LAMBDA;   /* RESET VALUE IN CONSTRAINTS MATRIX */
327 BLC[3,5] = LR;          /* RESET VALUE IN CONSTRAINTS MATRIX */
328
329 CALL NLPLM(RC,XR,"FCN",X,OPTN,BLC,TC,,,"DERIV"); /* LEVENBERG-MARQUARDT */
330
331 IF XI < 1E-7 THEN XI=0; /* ROUND SMALL VALUES OF XI TO ZERO */
332 L1_NORM = SUM(ABS(F));   /* L1 NORM */
333 IF RC>0 THEN CONVERGE='YES'; ELSE CONVERGE='NO'; /* RC IS RETURN CODE */
334 /* FROM NLPLM */
335 PRINT LABEL XI LAMBDA GAMMA DELTA L1_NORM;
336 APPEND; /* ADD OBSERVATIONS TO OUTPUT DATASET */
337 CONTINUE; /* GO TO NEXT OBSERVATION */
338
339 END; /* END OF DO LOOP PROCESSING */
340
341 QUIT; /* EXIT IML */
342
343 *----- PRINT RESULTS;
344
345 PROC PRINT DATA=RESULTS;
346 RUN;
347
348 *----- SAVE RESULTS TO AN EXCEL FILE;
349 *----- USER SUPPLIED OUTFILE IN PROC EXPORT;
350
351 PROC EXPORT DATA= WORK.RESULTS
352 OUTFILE= "filename"
353 DBMS=EXCEL REPLACE;
354 RUN;

```


Parresol, Bernard R.; Fonseca, Teresa Fidalgo; Marques, Carlos Pacheco. 2010.

Numerical details and SAS programs for parameter recovery of the S_B distribution.
Gen. Tech. Rep. SRS-122. Asheville, NC: U.S. Department of Agriculture Forest
Service, Southern Research Station. 27 p.

The four-parameter S_B distribution has seen widespread use in growth-and-yield modeling because it covers a broad spectrum of shapes, fitting both positively and negatively skewed data and bimodal configurations. Two recent parameter recovery schemes, an approach whereby characteristics of a statistical distribution are equated with attributes of a stand in order to solve for the parameters of the distribution, are described for the S_B . The first scheme permits recovery of the range and both shape parameters, but the location parameter must be a priori specified. The second scheme is an all-parameter recovery model. The details of the parameter recovery models, that is the system of equations with their concomitant constraints, are laid out. A solution technique for the constrained parameter recovery models that uses the Kuhn-Tucker conditions, the Lagrange function, and the Levenberg-Marquardt algorithm is briefly reviewed. Two Statistical Analysis System programs that implement the parameter recovery models, S_B Recovery 3parm and S_B Recovery 4parm, are listed and demonstrated with instructive examples.

Keywords: Basal area-size distribution, constraint functions, diameter distributions, moments, nonlinear programming problem, restricted estimation.



The Forest Service, United States Department of Agriculture (USDA), is dedicated to the principle of multiple use management of the Nation's forest resources for sustained yields of wood, water, forage, wildlife, and recreation. Through forestry research, cooperation with the States and private forest owners, and management of the National Forests and National Grasslands, it strives—as directed by Congress—to provide increasingly greater service to a growing Nation.

The USDA prohibits discrimination in all its programs and activities on the basis of race, color, national origin, age, disability, and where applicable, sex, marital status, familial status, parental status, religion, sexual orientation, genetic information, political beliefs, reprisal, or because all or part of an individual's income is derived from any public assistance program. (Not all prohibited bases apply to all programs.) Persons with disabilities who require alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD).

To file a complaint of discrimination, write to USDA, Director, Office of Civil Rights, 1400 Independence Avenue, SW, Washington, D.C. 20250-9410, or call (800) 795-3272 (voice) or (202) 720-6382 (TDD). USDA is an equal opportunity provider and employer.